



LED Wattage Chart

Drive Current	80L	96L
350 milliamps	-	100W
530 milliamps	-	151W
700 milliamps	170W	199W
1050 milliamps	263W	316W

FORM AND FUNCTION

- Sleek, low profile housing
- Engineered for optimum thermal management
- Low depreciation rate
- Optical system designed for Parking Structures

CONSTRUCTION

- Die Formed heavy duty Aluminum
- Corrosion resistant external hardware
- One-piece silicone gasket ensures IP-65 seal for electronics compartment
- Two-piece silicone Micro Optic system ensures IP-67 level seal around each PCB

BUY AMERICAN

To ensure the latest BAA/TAA/BABA Standards are being met, please select BAA, TAA, or BABA in the options section. Please contact the factory before placing an order for any NLS products requesting BAA (Buy American Act), TAA (Trade American Act), or BABA (Build America, Buy America).



Project Name:

Type:

VSR-2-PM ORDERING GUIDE

Cat#	Light Dist.	# of LEDs	Drive Current	Color Temp./CRI	Voltage
Value Series Round 2 (VSR-2)	Standard Silicone Micro Optics		Standard Configurations		Amber LED 595nm Dominant Wavelength Standard Turtle Friendly (AMBER) ^{1, 6, 7, 13} Amber LED Phosphor Converted (AMBER/PC) ^{1, 6, 7, 13} 2700K, 70 CRI (27K7) ² 2700K, 80 CRI (27K8) ² 3000K, 70 CRI (30K7) ² 3000K, 80 CRI (30K8) ² 3500K, 80 CRI (35K8) ² 4000K, 70 CRI (40K7) ² 4000K, 80 CRI (40K8) ² 5000K, 70 CRI (50K7) ² 5000K, 80 CRI (50K8) ²
	Type 2 (T2)	80 LED (80L)	700 mA (7)		
	Type 3 (T3)	96 LED (96L)	1050 mA (1)		
	Type 4 (T4)				
	Type 5 (T5)				
	Performance Silicone Micro Optics		Standard Configurations		
	Type 4 Forward Throw Wide (For Perimeters) (T4FTW)	80 LED (80L)	700 mA (7)		
	Type 5 Wide (T5W)	96 LED (96L)	1050 mA (1)		
			Performance Plus Configurations*		
			96 LED (96L)	350 mA (35) 530 mA (53)	

* Performance Plus configurations with our New Performance Silicone Optics.
(For the ultimate performance of the New Performance Silicone Optics combine highest chip count with High Efficacy Drive Currents)

* Performance Plus configurations with our New Performance Silicone Optics.
(For the ultimate performance of the New Performance Silicone Optics combine highest chip count with High Efficacy Drive Currents)

Mounting	Color	Controls Options	Options
Pendant Mount 12" Length (PM12)	Bronze Textured (BRZ)	Nema 7-Pin Receptacle (PE7)	Bird Spikes (BS)
Pendant Mount 24" Length (PM24)	White Textured (WHT)	Photocell + Receptacle (PCR)	Marine Grade Finish (MGF)
Pendant Mount 36" Length (PM36)	Smooth White Gloss (SWT)	Receptacle + Shorting Cap (PER)	Rotated Optic Left (ROL)
Pendant Mount Custom Length (PMX) ⁸	Silver Metallic (SVR)	FSP-211 w/Motion Sensor/Photocell (120/277VAC, 230-240VAC)	Rotated Optic Right (ROR)
	Black Textured (BLK)	8' Heights (FSP211-8) ^{4, 10}	Single Fuse (SF)
	Smooth Black Gloss (SBK)	9'-20' Heights (FSP211-20) ^{4, 10}	Double Fuse (DF)
	Graphite Textured (GPH)	21'-40' Heights (FSP211-40) ^{4, 10}	Black Optical Frame (BOF) ¹
	Grey Textured (GRY)	FSP-221 w/Motion Sensor/Photocell (100/347VAC, 208/230/480VAC)	House Side Shield (HSS) ⁵
	Green Textured (GRN)	8' Heights (FSP-HV-8) ¹¹	Buy American Act (BAA) ³
	Hunter Green Textured (HGN)	9'-20' Heights (FSP-HV-20) ¹¹	Trade Agreement Act (TAA) ³
	Custom (CS)	21'-40' Heights (FSP-HV-40) ¹¹	Build America Buy American (BABA) ³
		Custom Controls Integration (CCI) ⁹	
		Button Type Photocell (PC) ⁴	
		FSP Remote (FSIR) ¹²	
		DALI-2 (D2) ⁹	

NOTES:

1. Consult Factory for Lead Time
2. Consult Factory for 90 CRI Requests
3. Consult factory for all BAA/TAA/BABA requests
4. Universal Voltage 120V-277V
5. 3000K or lower, w/fixed mounting options only. Must be selected to meet International Dark-Sky Association certification
6. Turtle Safe
7. Not available above 530mA
8. Consult Factory for Custom Pendant Lengths
9. Please contact Factory for Custom Control Integration requests (nLight, NX, WaveLinx, Crestron, DMX/RDM, Synapse, Casambi, Dali II, Avi-On, or other control systems)
10. FSP-211, 120V/277V, 230-240VAC (single phase), 50/60Hz
11. FSP-221, 100-347VAC (single phase) or 208/230/480VAC (phase-to-phase)
12. Projects with sensors require Qty. 1 FSIR per project.
13. See estimated scaling chart for multiplier values to estimate lumen output Please contact Factory to verify the estimated performance data



701 Kingshill Place, Carson, CA 90746
Call Us Today (310) 341-2037

nlsighting.com

PRODUCT SPECIFICATIONS

ELECTRICAL

- 120-277 Volts (UNV) or 347-480 Volts (HV)
- 0-10V dimming driver
- Driver power factor at maximum load is $\geq .95$, THD maximum load is 15%
- LED Drivers Ambient Temp. Min is -40°C and Ambient Temp. Max ranges from 50°C to 55°C and, in some cases, even higher. Consult the factory for revalidation by providing the fixture catalog string before quoting and specifying it.
- All internal wiring UL certified for 600 VAC and 105°C
- All drivers, controls, and sensors housed in enclosed IP-65 compartment
- CRI 70, 80 or 90
- Color temperatures: Amber, 2700K, 3000K, 3500K, 4000K, 5000K
- Surge Protection: 20KA supplies as standard.

OPTIONS

- **BIRD SPIKES (BS)**—Offers effective and humane deterrent for larger bird species and provides cost-effective long-term solution to nuisance bird infestations and protect your property.
- **MARINE GRADE FINISH (MGF)**—A multi-step process creating protective finishing coat against harsh environments.
 - Chemically washed in a 5 stage cleaning system.
 - Pre-baked
 - Powder coated 3-5 mils of Zinc Rich Super Durable Polyester Primer.
 - 1-2 feet inside pole coverage top and bottom.
 - Oven Baked.
 - Finished Powder Coating of Super Durable Polyester Powder Coat 3-5 mil thickness.
- **HOUSE SIDE SHIELD**—House Side Shield (HSS) is designed for full property line cut-off.
- **ROUND POLE ADAPTER (RPA)**—When using round poles, specify Round Pole Adapter (RPA). Specify RPA4 when installing on 3"-4" round poles, and RPA5 when installing on 5"-6" round poles.
- **ROTATED OPTICS (ROL) (ROR)** - Rotated optics are designed for perimeter lighting for auto dealerships
- **BLACK OPTIC FRAME (BOF)** - Optional black optic frame. (includes black hardware) Standard is white

CONTROLS


- **FSP-211 w/Motion Sensor/Photocell (120/277VAC, 230-240VAC)** (FSP-X) - Passive infrared (PIR) sensor providing multi-level control based on motion/daylight contribution.
- **FSP-221 w/Motion Sensor/Photocell (100-347VAC, 208/230/480VAC)** (FSP-HV-X) - Passive infrared (PIR) sensor providing multi-level control based on motion/daylight contribution.
 - All control parameters adjustable via wireless configuration remote storing and transmitting sensor profiles.
 - FSP-8 mounting heights 8 feet and below
 - FSP-20 mounting heights 9-20 feet.
 - FSP-40 mounting heights 21-40 feet.
 - Includes 5 dimming event cycles, 0-10V dimming with motion sensing, re-programmable in the field.
 - FSIR-100 commissioning remote is required to change sensor settings. Please contact factory for ordering.

- **NEMA 7-PIN RECEPTACLE (PE7)**—An ANSI C136.41-2013 receptacle provides electrical and mechanical interconnection between photo control cell and luminaire. Dimming receptacle available two or four dimming contacts supports 0-10 VDC dimming methods or Digital Addressable Lighting Interface (DALI), providing reliable power interconnect.
- **Controls Agnostic:** Please contact factory for your preferred controls option. (nLight, NX, WaveLinx, Crestron, DMX/RDM, Synapse, Casambi, DALI II, Avi-On, or other control systems)

OPTICS

Silicone optics high photothermal stability and light output provides higher powered LEDs with minimized lumen depreciation LED life. UV and thermal stability with scratch resistance increases exterior application durability.

- IES Types



FINISH

- 5 mils electrostatic powder coat.
- NLS' standard high-quality finishes prevent corrosion protects against extreme environmental conditions.

WARRANTY

Five-year limited warranty for drivers and LEDs.

LISTINGS

- UL Listed in compliance with UL 1598, the Standard for Safety of Luminaires, including the applicable wet location requirements
- CSA C22.2 No. 250.0
- IP65/ IP67 Rated
- Dark Sky Approved
- IK10 Rated

BUY AMERICAN OPTION

While all of the NLS Lighting products listed in this document qualify for the Buy America(n) Act of 1933, we reserve the right to change our listings without notice.

The information provided above is for general informational purposes only. We encourage you to consult legal professionals for advice particular to your projects concerning BAA, TAA, BABA or Buy America.

Additional NLS Products that meet BAA, TAA standards can be found at the following link:

<https://nlsighting.com/buy-american/>



The information and specifications on this document are subject to change without any notification. All values are design, nominal, typical or prorated values when measured under internal and external laboratory conditions.



701 Kingshill Place, Carson, CA 90746
Call Us Today (310) 341-2037


nlsighting.com

PRODUCT SPECIFICATIONS


DIMENSION	VSR-2
A	21.5
B	6.5
Weight	24 lbs

EPA


EPA	SGL 12"	SGL 24"	SGL 36"
VSR-2-PM	.35	.38	.41



OPTICAL CONFIGURATIONS




VSR-2 / 80L




VSR-2 / 96L

PRODUCT SPECIFICATIONS


LED KELVIN RANGE




AMBER
585-600 nm




2700K 70 CRI




3000K 70 CRI



3500K 80 CRI



4000K 70 CRI



5000K 70 CRI

Color	Dominant or Peak Wavelength Range (nm)	
	Minimum	Maximum
Amber	585	600

Lumen Maintenance Data							
Ambient Temperature	Drive Current	L90 Hours*	L70 Hours	30,000 Hours*	50,000 Hours*	60,000 Hours*	100,000 Hours*
25°C	1050mA	38,000	96,000	93.0%	85.4%	81.8%	68.8%
*Reported extrapolations per IESNA TM-21				**Projected extrapolations per IESNA TM-21			

LUMEN MULTIPLIERS

Multipliers For 70/80/90 CRI (Scaling Factor from 5000K 70 CRI)			
CCT	70 CRI	80 CRI	90 CRI
2700K	0.840	0.737	0.609
3000K	0.975	0.776	0.640
3500K	0.890	0.800	0.659
4000K	1.000	0.815	0.679
5000K	1.000	0.830	0.710

Multipliers For Amber & PC Amber (Scaling Factor from 5000K 70 CRI)	
CCT	Multiplier
AMBER - Amber LED 595nm Dominant Wavelength - Standard Turtle Friendly	Consult Factory for estimated lumens and wattage
AMBER/PC - Amber LED Phosphor Converted	Consult Factory for estimated lumens and wattage

LENS MULTIPLIERS

Lens Type	Multiplier
CFL - Clear Tempered Glass Lens	0.8500
DPCL - Diffused Polycarbonate Visual Comfort Lens	0.6000
HAL - Yellow Polycarbonate Lens - less than 2% Blue Light Content	0.7000

PRODUCT SPECIFICATIONS

LUMEN CHARTS - STANDARD MICRO OPTICS

STANDARD SILICONE MICRO OPTICS - NON-SHIELDED - 80 LED

Part Number	T2	LPW	T3	LPW	T4	LPW	T5	LPW	Wattage
VSR-2-80L-1-27K7	25446	97	24813	94	24590	93	25660	98	263
VSR-2-80L-1-27K8	23829	91	23236	88	23028	88	24029	91	263
VSR-2-80L-1-30K7	27510	105	26826	102	26585	101	27741	105	263
VSR-2-80L-1-30K8	25548	97	24913	95	24689	94	25762	98	263
VSR-2-80L-1-35K8	25548	97	24913	95	24689	94	25762	98	263
VSR-2-80L-1-40K7	30261	115	29509	112	29244	111	30515	116	263
VSR-2-80L-1-40K8	28010	107	27314	104	27069	103	28245	107	263
VSR-2-80L-1-50K7	30261	115	29509	112	29244	111	30515	116	263
VSR-2-80L-1-50K8	28010	107	27314	104	27069	103	28245	107	263

STANDARD SILICONE MICRO OPTICS - NON-SHIELDED - 96 LED

Part Number	T2	LPW	T3	LPW	T4	LPW	T5	LPW	Wattage
VSR-2-96L-1-27K7	30574	97	29814	94	29546	94	30831	98	316
VSR-2-96L-1-27K8	28631	91	27919	88	27669	88	28872	91	316
VSR-2-96L-1-30K7	33054	105	32232	102	31943	101	33332	105	316
VSR-2-96L-1-30K8	30697	97	29933	95	29665	94	30955	98	316
VSR-2-96L-1-35K8	30697	97	29933	95	29665	94	30955	98	316
VSR-2-96L-1-40K7	36359	115	35455	112	35137	111	36665	116	316
VSR-2-96L-1-40K8	33654	107	32818	104	32523	103	33938	107	316
VSR-2-96L-1-50K7	36359	115	35455	112	35137	111	36665	116	316
VSR-2-96L-1-50K8	33654	107	32818	104	32523	103	33938	107	316

STANDARD SILICONE MICRO OPTICS - SHIELDED - 80 LED

Part Number	T3 HSS	LPW	T4 HSS	LPW	Wattage
VSR-2-80L-1-27K7-HSS	14110	54	13866	53	263
VSR-2-80L-1-27K8-HSS	13213	50	12985	49	263
VSR-2-80L-1-30K7-HSS	15254	58	14991	57	263
VSR-2-80L-1-30K8-HSS	14166	54	13922	53	263
VSR-2-80L-1-35K8-HSS	14166	54	13922	53	263
VSR-2-80L-1-40K7-HSS	17358	66	17095	65	263
VSR-2-80L-1-40K8-HSS	16067	61	15823	60	263
VSR-2-80L-1-50K7-HSS	17358	66	17095	65	263
VSR-2-80L-1-50K8-HSS	16067	61	15823	60	263

STANDARD SILICONE MICRO OPTICS - SHIELDED - 96 LED

Part Number	T3 HSS	LPW	T4 HSS	LPW	Wattage
VSR-2-96L-1-27K7-HSS	16953	54	16661	53	316
VSR-2-96L-1-27K8-HSS	15875	50	15602	49	316
VSR-2-96L-1-30K7-HSS	18328	58	18012	57	316
VSR-2-96L-1-30K8-HSS	17021	54	16727	53	316
VSR-2-96L-1-35K8-HSS	17021	54	16727	53	316
VSR-2-96L-1-40K7-HSS	20856	66	20540	65	316
VSR-2-96L-1-40K8-HSS	19305	61	19012	60	316
VSR-2-96L-1-50K7-HSS	20856	66	20540	65	316
VSR-2-96L-1-50K8-HSS	19305	61	19012	60	316

PRODUCT SPECIFICATIONS

LUMEN CHARTS - PERFORMANCE MICRO OPTICS

PERFORMANCE SILICONE MICRO OPTICS - NON-SHIELDED - 80 LED					
Part Number	T4FTW	LPW	T5W	LPW	Wattage
VSR-2-80L-7-27K7	17025	100	19644	116	170
VSR-2-80L-7-27K8	15943	94	18396	108	170
VSR-2-80L-7-30K7	18409	108	21241	125	170
VSR-2-80L-7-30K8	17096	101	19726	116	170
VSR-2-80L-7-35K8	17096	101	19726	116	170
VSR-2-80L-7-40K7	19890	117	22950	135	170
VSR-2-80L-7-40K8	18411	108	21243	125	170
VSR-2-80L-7-50K7	19890	117	22950	135	170
VSR-2-80L-7-50K8	18411	108	21243	125	170
VSR-2-80L-1-27K7	24786	98	25904	102	254
VSR-2-80L-1-27K8	23211	91	24258	96	254
VSR-2-80L-1-30K7	26799	106	28061	110	254
VSR-2-80L-1-30K8	24888	98	26060	103	254
VSR-2-80L-1-35K8	24888	98	26060	103	254
VSR-2-80L-1-40K7	28956	114	30320	119	254
VSR-2-80L-1-40K8	26802	106	28065	110	254
VSR-2-80L-1-50K7	28956	114	30320	119	254
VSR-2-80L-1-50K8	26802	106	28065	110	254

PERFORMANCE SILICONE MICRO OPTICS - NON-SHIELDED - 96 LED					
Part Number	T4FTW	LPW	T5W	LPW	Wattage
VSR-2-96L-35-27K7	11128	111	12069	121	100
VSR-2-96L-35-27K8	10421	104	11302	113	100
VSR-2-96L-35-30K7	12032	120	13050	130	100
VSR-2-96L-35-30K8	11173	112	12078	121	100
VSR-2-96L-35-35K8	11173	112	12078	121	100
VSR-2-96L-35-40K7	13000	130	14100	141	100
VSR-2-96L-35-40K8	12033	120	13051	131	100
VSR-2-96L-35-50K7	13000	130	14100	141	100
VSR-2-96L-35-50K8	12033	120	13051	131	100
VSR-2-96L-53-27K7	16028	106	18613	123	151
VSR-2-96L-53-27K8	15009	99	17430	115	151
VSR-2-96L-53-30K7	17329	115	20124	133	151
VSR-2-96L-53-30K8	16093	107	18689	124	151
VSR-2-96L-53-35K8	16093	107	18689	124	151
VSR-2-96L-53-40K7	18724	124	21744	144	151
VSR-2-96L-53-40K8	17331	115	20127	133	151
VSR-2-96L-53-50K7	18724	124	21744	144	151
VSR-2-96L-53-50K8	17331	115	20127	133	151
VSR-2-96L-7-27K7	20100	101	22826	115	199
VSR-2-96L-7-27K8	18823	95	21375	107	199
VSR-2-96L-7-30K7	21733	109	24680	124	199
VSR-2-96L-7-30K8	20183	101	22919	115	199
VSR-2-96L-7-35K8	20183	101	22919	115	199
VSR-2-96L-7-40K7	23482	118	26666	134	199
VSR-2-96L-7-40K8	21735	109	24682	124	199
VSR-2-96L-7-50K7	23482	118	26666	134	199
VSR-2-96L-7-50K8	21735	109	24682	124	199
VSR-2-96L-1-27K7	28505	95	31145	104	299
VSR-2-96L-1-27K8	26693	89	29166	98	299
VSR-2-96L-1-30K7	30819	103	33673	113	299
VSR-2-96L-1-30K8	28621	96	31271	105	299
VSR-2-96L-1-35K8	28621	96	31271	105	299
VSR-2-96L-1-40K7	33300	111	36384	122	299
VSR-2-96L-1-40K8	30823	103	33678	113	299
VSR-2-96L-1-50K7	33300	111	36384	122	299
VSR-2-96L-1-50K8	30823	103	33678	113	299

PRODUCT SPECIFICATIONS

BUG RATING CHARTS - STANDARD MICRO OPTICS

STANDARD SILICONE MICRO OPTICS - NON-SHIELDED - 80 LED				
Part Number	T2	T3	T4	T5
VSR-2-80L-1-27K7	B3-U0-G3	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-27K8	B3-U0-G3	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-30K7	B3-U0-G3	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-30K8	B3-U0-G3	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-35K8	B3-U0-G3	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-40K7	B3-U0-G3	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-40K8	B3-U0-G3	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-50K7	B3-U0-G3	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-50K8	B3-U0-G3	B3-U0-G4	B3-U0-G4	B5-U0-G4

STANDARD SILICONE MICRO OPTICS - NON-SHIELDED - 96 LED				
Part Number	T2	T3	T4	T5
VSR-2-96L-1-27K7	B3-U0-G4	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-27K8	B3-U0-G4	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-30K7	B3-U0-G4	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-30K8	B3-U0-G4	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-35K8	B3-U0-G4	B3-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-40K7	B4-U0-G4	B4-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-40K8	B4-U0-G4	B4-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-50K7	B4-U0-G4	B4-U0-G4	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-50K8	B4-U0-G4	B4-U0-G4	B3-U0-G4	B5-U0-G4

STANDARD SILICONE MICRO OPTICS - SHIELDED - 80 LED		
Part Number	T3 HSS	T4 HSS
VSR-2-80L-1-27K7	B1-U0-G3	B1-U0-G3
VSR-2-80L-1-27K8	B1-U0-G3	B1-U0-G3
VSR-2-80L-1-30K7	B1-U0-G3	B1-U0-G3
VSR-2-80L-1-30K8	B1-U0-G3	B1-U0-G3
VSR-2-80L-1-35K8	B1-U0-G3	B1-U0-G3
VSR-2-80L-1-40K7	B1-U0-G3	B1-U0-G3
VSR-2-80L-1-40K8	B1-U0-G3	B1-U0-G3
VSR-2-80L-1-50K7	B1-U0-G3	B1-U0-G3
VSR-2-80L-1-50K8	B1-U0-G3	B1-U0-G3

STANDARD SILICONE MICRO OPTICS - SHIELDED - 96 LED		
Part Number	T3 HSS	T4 HSS
VSR-2-96L-1-27K7	B1-U0-G3	B1-U0-G3
VSR-2-96L-1-27K8	B1-U0-G3	B1-U0-G3
VSR-2-96L-1-30K7	B1-U0-G3	B1-U0-G3
VSR-2-96L-1-30K8	B1-U0-G3	B1-U0-G3
VSR-2-96L-1-35K8	B1-U0-G3	B1-U0-G3
VSR-2-96L-1-40K7	B1-U0-G4	B1-U0-G4
VSR-2-96L-1-40K8	B1-U0-G4	B1-U0-G4
VSR-2-96L-1-50K7	B1-U0-G4	B1-U0-G4
VSR-2-96L-1-50K8	B1-U0-G4	B1-U0-G4

PRODUCT SPECIFICATIONS

BUG RATING CHARTS - PERFORMANCE MICRO OPTICS

PERFORMANCE SILICONE MICRO OPTICS - NON-SHIELDED - 80 LED		
Part Number	T4FTW	T5W
VSR-2-80L-1-27K7	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-27K8	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-30K7	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-30K8	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-35K8	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-40K7	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-40K8	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-50K7	B3-U0-G4	B5-U0-G4
VSR-2-80L-1-50K8	B3-U0-G4	B5-U0-G4

PERFORMANCE SILICONE MICRO OPTICS - NON-SHIELDED - 96 LED		
Part Number	T4FTW	T5W
VSR-2-96L-35-27K7	B2-U0-G3	B4-U0-G3
VSR-2-96L-35-27K8	B2-U0-G3	B4-U0-G3
VSR-2-96L-35-30K7	B2-U0-G3	B4-U0-G3
VSR-2-96L-35-30K8	B2-U0-G3	B4-U0-G3
VSR-2-96L-35-35K8	B2-U0-G3	B4-U0-G3
VSR-2-96L-35-40K7	B2-U0-G3	B4-U0-G3
VSR-2-96L-35-40K8	B2-U0-G3	B4-U0-G3
VSR-2-96L-35-50K7	B2-U0-G3	B4-U0-G3
VSR-2-96L-35-50K8	B2-U0-G3	B4-U0-G3
VSR-2-96L-53-27K7	B3-U0-G3	B5-U0-G3
VSR-2-96L-53-27K8	B3-U0-G3	B4-U0-G3
VSR-2-96L-53-30K7	B3-U0-G3	B5-U0-G3
VSR-2-96L-53-30K8	B3-U0-G3	B5-U0-G3
VSR-2-96L-53-35K8	B3-U0-G3	B5-U0-G3
VSR-2-96L-53-40K7	B3-U0-G4	B5-U0-G3
VSR-2-96L-53-40K8	B3-U0-G3	B5-U0-G3
VSR-2-96L-53-50K7	B3-U0-G4	B5-U0-G3
VSR-2-96L-53-50K8	B3-U0-G3	B5-U0-G3
VSR-2-96L-7-27K7	B3-U0-G4	B5-U0-G3
VSR-2-96L-7-27K8	B3-U0-G4	B5-U0-G3
VSR-2-96L-7-30K7	B3-U0-G4	B5-U0-G4
VSR-2-96L-7-30K8	B3-U0-G4	B5-U0-G3
VSR-2-96L-7-35K8	B3-U0-G4	B5-U0-G3
VSR-2-96L-7-40K7	B3-U0-G4	B5-U0-G4
VSR-2-96L-7-40K8	B3-U0-G4	B5-U0-G4
VSR-2-96L-7-50K7	B3-U0-G4	B5-U0-G4
VSR-2-96L-7-50K8	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-27K7	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-27K8	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-30K7	B3-U0-G5	B5-U0-G4
VSR-2-96L-1-30K8	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-35K8	B3-U0-G4	B5-U0-G4
VSR-2-96L-1-40K7	B3-U0-G5	B5-U0-G4
VSR-2-96L-1-40K8	B3-U0-G5	B5-U0-G4
VSR-2-96L-1-50K7	B3-U0-G5	B5-U0-G4
VSR-2-96L-1-50K8	B3-U0-G5	B5-U0-G4

PRODUCT SPECIFICATIONS

PENDANT MOUNT (PMX)

Available lengths:


12" length (PM12)

24" Length (PM24)

36" Length (PM36)

Custom Length (PMX)

*Consult factory for custom lengths



PRODUCT SPECIFICATIONS

CONTROL OPTIONS

DIMMING CONTROL (FSP)—Passive infrared (PIR) sensor providing multi-level control based on motion/daylight contribution

All control parameters adjustable via wireless configuration remote storing and transmitting sensor profiles.

FSP-8 mounting heights 8 feet and below

FSP-20 mounting heights 9-20 feet.

FSP-40 mounting heights 21-40 feet.

Includes 5 dimming event cycles, 0-10V dimming with motion sensing, re-programmable in the field.

FSP-211 WITH MOTION SENSOR (FSP-XX)

FSP-211(FSP-X)—Passive infrared (PIR) sensor providing multi-level control based on motion/daylight contribution.

120/277VAC, 230-240VAC

All control parameters adjustable via wireless configuration remote storing and transmitting sensor profiles.


FSP-8 mounting heights 8 feet and below

FSP-20 mounting heights 9-20 feet.

FSP-40 mounting heights 21-40 feet.

Includes 5 dimming event cycles, 0-10V dimming with motion sensing, re-programmable in the field.

FSP-211



FSP-221 WITH MOTION SENSOR (FSP-HV-XX)

FSP-221 (FSP-HV-X)—Passive infrared (PIR) sensor providing multi-level control based on motion/daylight contribution.

100-347VAC 208/230/480VAC

All control parameters adjustable via wireless configuration remote storing and transmitting sensor profiles.


FSP-8 mounting heights 8 feet and below

FSP-20 mounting heights 9-20 feet.

FSP-40 mounting heights 21-40 feet.



Includes 5 dimming event cycles, 0-10V dimming with motion sensing, re-programmable in the field.

FSP-221





FSP-8

Coverage Top View @ 12ft.





FSP-20

Coverage Top View @ 20 ft.



FSP-40


Coverage Top View @ 40ft



PRODUCT SPECIFICATIONS


PHOTOCELL + RECEPTACLE (PCR)

7-Pin Receptacle and Electronic Twist Lock Photocell for dusk to dawn operation.




RECEPTACLE + SHORTING CAP (PER)

7-Pin Receptacle and Shorting Cap.



NEMA 7-PIN RECEPTACLE (PE7)


An ANSI C136.41-2013 receptacle provides electrical and mechanical interconnection between photo control cell and luminaire. Dimming receptacle available two or four dimming contacts supports 0-10 VDC dimming methods or Digital Addressable Lighting Interface (DALI), providing reliable power interconnect.



PRODUCT SPECIFICATIONS

BIRD SPIKES (BS)

Bird Spikes offers effective and humane deterrent for larger bird species and provides cost-effective long-term solution to nuisance bird infestations and protect your property.



MARINE GRADE FINISH (MGF)

The **(MGF)** is a multi step process. Chemically washed in a 5 stage cleaning system. Pre-baked. Powder coated 3-5 mils of Zinc Rich Super Durable Polyester Primer. Oven Baked. Finished Powder Coating of Super Durable Polyester Powder Coat 3-5 mil thickness.



Powder Coat Finish

3-5 mil Powder Coat

Primer Layer

3-5 mil Zinc Rich Super Durable Polyester Primer

Prepared Casting

Chemically washed in multi Step 5 stage cleaning process

BUTTON PHOTOCELL

Photo Cell for dusk to dawn operation.

